

HYDROGEN

Safety Data Sheet



1. IDENTIFICATION

Product identifier

Product Name HYDROGEN

Other means of identification

Safety data sheet number LIND-P066

UN/ID no. UN1049

Synonyms Gourmet H, Grade 5.5, Grade 5.3, Grade 5.0, Grade 4.0, Zero Gas

Recommended use of the chemical and restrictions on use

Recommended Use Industrial and professional use. Food and Beverage. Calibration/test gas.

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Messer North America, Inc. - Messer LLC - Messer Merchant Production LLC

200 Somerset Corporate Blvd, Suite 7000

Bridgewater, NJ 08807

Phone: 908-464-8100

www.messer-us.com

Messer Gas Puerto Rico, Inc.

Road 869, Km 1.8

Barrio Palmas, Catano, PR 00962

Phone: 787-641-7445

* May include subsidiaries or affiliate companies/divisions.

For additional product information contact your local customer service.

Emergency telephone number

Company Phone Number +1 800-232-4726 (Messer National Operations Center, US)

CHEMTREC: 1-800-424-9300 (North America) +1-703-527-3887 (International)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Flammable gases	Category 1
Gases under pressure	Compressed gas
Simple asphyxiants	Yes

Label elements



Signal word

Danger

Hazard Statements

Extremely flammable gas
 Contains gas under pressure; may explode if heated
 May displace oxygen and cause rapid suffocation
 May form explosive mixtures with air
 Burns with invisible flame

Precautionary Statements - Prevention

Do not handle until all safety precautions have been read and understood
 Keep away from heat, sparks, open flames, hot surfaces. — No smoking
 Use and store only outdoors or in a well ventilated place
 Use a backflow preventive device in piping
 Use only with equipment rated for cylinder pressure
 Do not open valve until connected to equipment prepared for use
 Close valve after each use and when empty

Precautionary Statements - Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention/advice.
 Leaking gas fire: do not extinguish, unless leak can be stopped safely.
 Eliminate all ignition sources if safe to do so.

Precautionary Statements - Storage

Protect from sunlight when ambient temperature exceeds 52°C/125°F

Hazards not otherwise classified (HNOC)

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure Gas

Chemical Name	CAS No.	Volume %	Chemical Formula
HYDROGEN	1333-74-0	>99	H ₂

4. FIRST AID MEASURES

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Skin contact	None under normal use. Get medical attention if symptoms occur.
Eye contact	None under normal use. Get medical attention if symptoms occur.
Ingestion	Not an expected route of exposure.
Self-protection of the first aider	RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Symptoms	Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical or CO₂. Water spray (fog). DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific extinguishing methods

If possible, stop the flow of gas. Do not extinguish the fire until supply is shut off as otherwise an explosive-ignition may occur. If the fire is extinguished and the flow of gas continues, use increased ventilation to prevent build-up of explosive atmosphere. Ventilation fans must be explosion proof. Use non-sparking tools to close container valves.

Use water spray to cool surrounding containers. Be cautious of a Boiling Liquid Evaporating Vapor Explosion, BLEVE, if flame is impinging on surrounding containers. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Damaged cylinders should be handled only by specialists.

Specific hazards arising from the chemical

Extremely flammable gas. May form explosive mixtures with air. Hydrogen is very light and may collect in the upper portions of storage areas. Hydrogen burns with an almost invisible flame. High pressure releases may ignite with no apparent ignition source possibly via static electricity. Vapors may travel to source of ignition and flash back. Cylinders may rupture under extreme heat.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, NIOSH (approved or equivalent) and full protective gear. As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Monitor oxygen level. Consider the risk of potentially explosive atmospheres. All equipment used when handling the product must be grounded. Use non-sparking tools and equipment. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Environmental precautions

Environmental precautions Prevent spreading of vapors through sewers, ventilation systems and confined areas.

Methods and material for containment and cleaning up

Methods for containment Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is in container or container valve, contact the appropriate emergency telephone number in Section 1 or call your closest Messer location.

Methods for cleaning up Return cylinder to Messer or an authorized distributor.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Ground and bond all lines and equipment associated with product system. All equipment should be non-sparking and explosion proof Separate flammable gas cylinders from oxygen and other oxidizers by a minimum distance of 20 ft. or by a 5 ft. high barrier with a minimum fire resistance rating of a half an hour. "NO SMOKING" signs should be posted in storage and use areas. Hydrogen is non-corrosive. However hydrogen can interact with metals (hardened steels) to cause embrittlement.

Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Never attempt to lift a cylinder by its valve protection cap. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing leak to occur. Use an adjustable strap wrench to remove over-tight or rusted caps. Use only with adequate ventilation. Use a backflow preventive device in piping. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Ensure the complete gas system has been checked for leaks before use.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

Only experienced and properly instructed persons should handle gases under pressure. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, publication CGA-P1, Safe Handling of Compressed Gases in Containers.

For additional recommendations, consult Compressed Gas Association's publications G-5, G-5.3, G-5.5, P-6 and P-76. NFPA 50A covers gaseous hydrogen at consumer sites.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Keep at temperatures below 52°C / 125°F. Cylinders

should be stored upright with valve protection cap in place and firmly secured to prevent falling. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Full and empty cylinders should be segregated. Stored containers should be periodically checked for general condition and leakage. Outside or detached storage is preferred.

Incompatible materials Oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
HYDROGEN 1333-74-0	: See Appendix F: Minimal Oxygen Content	None	None

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Provide general ventilation, local exhaust ventilation, process enclosure or other engineering controls to maintain airborne levels below recommended exposure limits and to maintain oxygen levels above 19.5%. Explosion proof ventilation systems. Oxygen detectors should be used when asphyxiating gases may be released. Consider installation of leak detection systems in areas of use and storage. Systems under pressure should be regularly checked for leakages.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Work gloves and safety shoes are recommended when handling cylinders. Wear fire/flame resistant/retardant clothing. Take precautionary measures against static discharge.

Respiratory protection Use positive pressure airline respirator with escape cylinder or self contained breathing apparatus for oxygen-deficient atmospheres (<19.5%).

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Gas
Appearance	Colorless
Odor	Odorless
Odor threshold	No information available
pH	Not applicable
Melting/freezing point	-259.2 °C / -434.8 °F
Boiling point / boiling range	-253 °C / -423 °F
Evaporation rate	Not applicable
Flammability (solid, gas)	Flammable Gas
Lower flammability limit:	4%
Upper flammability limit:	75%
Flash point	Not applicable
Autoignition temperature	570 °C / 1058 °F
Decomposition temperature	No data available
Water solubility	0.019 vol/vol @ 15.6°C
Partition coefficient	No data available
Kinematic viscosity	Not applicable

Component Level Information:

Chemical Name	Molecular weight	Boiling point/range	Vapor Pressure	Vapor density (air =1)	Gas Density kg/m ³ @20°C	Critical Temperature
HYDROGEN	1.00	-252.8 °C	Above critical temperature	0.07	0.083	-240 °C

10. STABILITY AND REACTIVITY**Reactivity**

Not reactive under normal conditions

Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Yes.

Possibility of Hazardous Reactions

May form explosive mixtures with air. May react violently with oxidizers.

Conditions to avoid

Heat, flames and sparks. Flammable or explosive when mixed with chlorine or other oxidizing materials. Fluorine and hydrogen react at -418°F (-250°C) when impurities are present. Chlorine/hydrogen mixtures explode if exposed to light. Lithium metal will burn in a hydrogen atmosphere.

Incompatible materials

Oxidizing agents.

Hazardous Decomposition Products

None known.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation	Product is a simple asphyxiant.
Skin contact	No data available
Eye contact	No data available
Ingestion	Not an expected route of exposure.

Information on toxicological effects

Symptoms	Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to oxygen-deficient atmosphere (<=19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious injury or death.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Not classified.
-------------------	-----------------

Sensitization	Not classified.
Germ cell mutagenicity	Not classified.
Carcinogenicity	This product does not contain any carcinogens or potential carcinogens listed by OSHA, IARC or NTP.
Reproductive toxicity	Not classified.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified.
Chronic toxicity	None known.
Aspiration hazard	Not applicable.

Numerical measures of toxicity

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	Inhalation LC50 (CGA P-20)
HYDROGEN 1333-74-0	-	-	> 15000 ppm (Rat) 1 h	-

Product Information

Oral LD50	No information available
Dermal LD50	No information available.
Inhalation LC50	No information available

12. ECOLOGICAL INFORMATION**Ecotoxicity**

No known acute aquatic toxicity.

Persistence and degradability

No information available.

Bioaccumulation

No information available.

13. DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP IN PLACE to Messer for proper disposal.

14. TRANSPORT INFORMATION**DOT**

UN/ID no.	UN1049
Proper shipping name	Hydrogen, compressed
Hazard Class	2.1
Special Provisions	N89
Description	UN1049, Hydrogen, compressed, 2.1
Emergency Response Guide Number	115

TDG

UN/ID no.	UN1049
Proper shipping name	Hydrogen, compressed
Hazard Class	2.1
Description	UN1049 Hydrogen, compressed 2.1

IATA

UN/ID no.	UN1049
Proper shipping name	Hydrogen, compressed
Hazard Class	2.1
ERG Code	10L
Special Provisions	A1
Description	UN1049, Hydrogen, compressed, 2.1

IMDG

UN/ID no.	UN1049
Proper shipping name	Hydrogen, compressed
Hazard Class	2.1
EmS-No.	F-D, S-U
Description	UN1049, Hydrogen, compressed, 2.1

15. REGULATORY INFORMATION

INTERNATIONAL INVENTORIES

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

US FEDERAL REGULATIONS

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Risk and Process Safety Management Programs

This material, as supplied, contains one or more regulated substances with specified thresholds under 40 CFR Part 68 or regulated as a highly hazardous chemical pursuant to the 29 CFR Part 1910.110 with specified thresholds:

Chemical Name	U.S. - CAA (Clean Air Act) - Accidental Release Prevention - Toxic Substances	U.S. - CAA (Clean Air Act) - Accidental Release Prevention - Flammable Substances	U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals
HYDROGEN		10000 lb	

US STATE REGULATIONS

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania

Hydrogen 1333-74-0	X	X	X
-----------------------	---	---	---

16. OTHER INFORMATION

NFPA **Health hazards** 0 **Flammability** 4 **Instability** 0 **Physical and Chemical Properties** -

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2019, CGA Recommended Hazard Ratings for Compressed Gases, 4th Edition.

Issue Date 24-Feb-2015
Revision Date 17-Mar-2021
Revision Note SDS sections updated; 1

LIND-PO66

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Messer LLC, Messer Merchant Production LLC, Messer North America, Inc., Messer Gas Puerto Rico, Inc. or Messer Canada Inc. (or any of their affiliates and subsidiaries) and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet